



Water Conditioning for the 21st Century
 Eco-Friendly – Maintenance Free – 5 Year Ltd. Warranty

SPECIFICATIONS

3/8” RESIDENTIAL ECOFLOW

Part No.	Size	Body Length		Overall Length with Ends		Body O.D.		Available Ends	Max Flow Rate		Weight	
		in	cm	in	cm	in	cm		gpm	L/min	lbs.	kg.
EFR-38-4	3/8”	10	25.40	10.45	26.54	1.9”	4.826	3/8” FPT	4.0	15.14	3.7	1.678



WHEN ORDERING
 3/8” MIPT x 1/4” Compression SST or
 3/8” MIPT x 3/8” Compression SST

Note that they are available but not included in the price.

Common Unit Specifications

- **Pressure Loss** of 1.10 PSI or less for 1/4” outlet.
- **Pressure Loss** of 0.45 PSI or less for 3/8” outlet.
- **Maximum Pressure Rating** of 150 PSI.
- Each unit is Hydrostatically Tested.

Materials of Construction

- **Internal Liner** is constructed of Type L Copper Tubing conforming to ASTM B88.
- **External Body and Fittings** are 304 Stainless Steel conforming to ASME A778.
- **Threaded Ends x FPT** are 304 Stainless Steel conforming to ASME A778.

Due to our ongoing research and product development program the above mentioned specifications are subject to change without notice.

