



Water Conditioning for the 21st Century
 Eco-Friendly – Maintenance Free – 5 Year Ltd. Warranty

SPECIFICATIONS

1” Thru 2”

FOR LIGHT INDUSTRIAL AND RESIDENTIAL

Part No.	Size	Length		Overall Length with Ends		Body O.D. (MPT/FPT)		Available Ends	Max Flow Rate		Weight	
		in	cm	in	cm	in	cm		gpm	L/min	lbs.	kg.
EFR-0100-26	1”	15 ½	39.37	19 5/8	49.85	2 7/8	7.303	1”	26	98.42	18.05	8.19
EFR-0200-52	2”	15	38.10	22 3/8	56.83	3 ½	8.890	2”	52	196.84	24.75	11.23



WHEN ORDERING: SPECIFY WATER SUPPLY LINE SIZE SO THAT PROPER THREADED ENDS CAN BE SENT WITH YOUR ECOFLOW UNIT

Common Unit Specifications

- Pressure Loss of 3 PSI or less for Each Unit
- Maximum Pressure Rating of 150 PSI
- Flow Rates Validated through the Center for Irrigation Technology(CIT), University of California, Fresno
- Each unit is Hydrostatically Tested.

Materials of Construction

- Internal Body is constructed of Type L Copper Tubing conforming to ASTM B88.
- External Body and Fittings are 304 Stainless Steel conforming to ASME A778
- Threaded Ends x Tri-Clover are 304 Stainless Steel conform to ASME A778

Due to our ongoing research and product development program the above mentioned specifications are subject to change without notice.

