



Water Conditioning for the 21st Century
 Eco-Friendly – Maintenance Free – 5 Year Ltd. Warranty

SPECIFICATIONS

3/8” RESIDENTIAL ECOFLOW

PART NO.	OUTLET SIZE	BODY LENGTH	OVERALL LENGTH W/ ENDS	BODY O.D.	AVAILABLE ENDS	MAX FLOW RATE (GPM)	WEIGHT (lbs.)
EFR-38-4	3/8”	10”	10.45”	1.9”	3/8” FPT	4.0	3.7



WHEN ORDERING

*3/8” MIPT x 1/4” Compression SST or
 3/8” MIPT x 3/8” Compression SST*

Note that they are available but not included in the price.

Common Unit Specifications

- **Pressure Loss** of 1.10 PSI or less for 1/4” outlet.
- **Pressure Loss** of 0.45 PSI or less for 3/8” outlet.
- **Maximum Pressure Rating** of 150 PSI.
- Each unit is Hydrostatically Tested.

Materials of Construction

- **Internal Liner** is constructed of Type L Copper Tubing conforming to ASTM B88.
- **External Body and Fittings** are 304 Stainless Steel conforming to ASME A778.
- **Threaded Ends x FPT** are 304 Stainless Steel conforming to ASME A778.

Due to our ongoing research and product development program the above mentioned specifications are subject to change without notice.

©2014 Morrill Industries, Inc.

24754 East River Road Escalon, CA 95320

Phone: (209)838-2550 Fax: (209)838-3544

Website: www.morrillinc.com and www.ecoflow.co

