



Water Conditioning for the 21st Century
 Eco-Friendly – Maintenance Free – 5 Year Ltd. Warranty

SPECIFICATIONS

1" THRU 2"

FOR LIGHT INDUSTRIAL AND RESIDENTIAL

PART NO.	SIZE	BODY LENGTH	OVERALL LENGTH W/ ENDS	BODY O.D.	Available Ends	MAX FLOW RATE (GPM)	WEIGHT (LBS.)
EFR-341-26	3/4" - 1"	16"	19-3/4"	2-7/8"	3/4" or 1" MPT/FPT	26	12.1
EFR-152-52	1-1/2" - 2"	18-1/2"	22-1/2"	3-1/2"	1-1/2" or 2" MPT/FPT	52	18.3



WHEN ORDERING: SPECIFY WATER SUPPLY LINE SIZE SO THAT PROPER THREADED ENDS CAN BE SENT WITH YOUR ECOFLOW UNIT

Common Unit Specifications

- **Pressure Loss** of 3 PSI or less for Each Unit
- **Maximum Pressure Rating** of 150 PSI
- Flow Rates Validated through the Center for Irrigation Technology(CIT), University of California, Fresno
- Each unit is Hydrostatically Tested.

Materials of Construction

- Internal Body is constructed of Type L Copper Tubing conforming to ASTM B88.
- External Body and Fittings are 304 Stainless Steel conforming to ASME A778
- Threaded Ends x Tri-Clover are 304 Stainless Steel conform to ASME A778

Due to our ongoing research and product development program the above mentioned specifications are subject to change without notice.

©2014 Morrill Industries, Inc.

24754 East River Road Escalon, CA 95320

Phone: (209)838-2550 Fax: (209)838-3544

Website: www.morrillinc.com and www.ecoflow.co

